## MAINTENANCE SCHEDULE

Perform the pre-ride inspection (page 36) at each scheduled maintenance period.

## I: INSPECT C: CLEAN R: REPLACE A: ADJUST L: LUBRICATE O: OIL CHANGE T: TOP UP E: EMISSION CHECK

The following maintenance schedule specifies all maintenance required to keep your vehicle in peak operating condition. Maintenance work should be performed in accordance with standards and specifications of Hero MotoCorp by properly trained and equipped technicians. Your Authorised Hero MotoCorp workshop meets all of these requirements.

Ensure that each paid service is availed within 90 days or 3000 km from the date of previous service, whichever is earlier.

- To be serviced by your Authorised Hero MotoCorp workshop unless the owner has the relevant tools, technical information and is technically qualified.
- In the interest of safety, we recommend that these jobs are carried out only by your Authorised Hero MotoCorp workshop.
- **Note-1**: At higher odometer readings, repeat the frequency interval established here.
- **Note-2**: Service more frequently if the vehicle is ridden in unusually wet or dusty areas.
- Note-3 : Replace engine oil once in every 6000 km. Top up if the oil level is at or near the lower level mark.
- **Note-4**: Visit Authorised Hero MotoCorp workshop for inspection, cleaning, lubrication and adjustment of drive chain at every **700** km.
- **Note-5**: Replace brake fluid once in every two years or 30000 km, whichever is earlier.
- Note-6 : Inspect & maintain specified torque.
- **Note-7**: Inspect the wheel bearings free play, replace if necessary.
- **Note-8** : Replace front fork oil once in a every 2 years or  $30000 \, \text{km}$ , whichever is earlier.
- **Note-9**: Inspect rear suspension mounting bushes play, replace rear shock absorber if necessary.
- Note-10: Check CO emission at idle.
- **Note-11:** Inspect the canister hoses for deterioration, damage or loose connections and canister for cracks or other damages.

**Note:** Always wipe the water from the vehicle after washing. Use clean soft cloth or pressurized air for completely drying the water.

## MAINTENANCE SCHEDULE

## Dear Customer,

We would strongly recommend the following schedule, to keep your vehicle in perfect running condition and healthy environment. Vehicle subjected to severe use or ridden in dusty area will require more frequent servicing.

ITEMS		WHICHEVER COMES FIRST	DURING FREE SERVICE PERIOD						AFTER	R FREE SE	ERVICE		
		SERVICE	<b>1</b> *t	2 <sup>nd</sup>	3 <sup>rd</sup>	4 <sup>th</sup>	5 <sup>th</sup>	ONCE IN EVERY					
		DAYS	1st 60	Next 100 3000- 3500	Next 100 6000- 6500	Next 100 9000- 9500	Next 100 12000- 12500						
		KM Note-1	500- 750					3000	6000	9000	12000	15000	
	Fuel Line		I	I	I	I	I	I					
1	Throttle Operation		I, A	I, A	I, A	I, A	I, A	I, A					
1	Air Cleaner Element	Note-2	С	С	С	С	R	С			R		
	Spark Plug		I, C, A	I, C, A	I, C, A	I, C, A	R	I, C, A			R		
×	Valve Clearance		I, A	I, A	I, A	I, A	I, A	I, A					
	Engine Oil	Note-3	0	I, T	0	I, T	0	I, T	0				
*	Engine Oil Strainer Screen		С		С		С		С				
*	Engine Oil Centrifugal Filter		С		С		С		С				
1	Engine Oil Cooler & Hoses		I	I	I	I	I	I					
	Electric Starter		I	I	I	I	I	I					
	Oil Circulation		I	I	I	I	I	I					
×	Drive Chain	Note-4	I,C,L,A at every 700 km					I,C,L,A at every 700 km					
	Drive Chain Slider			I	I	I	I	I					

		WHICHEVER COMES FIRST							AFTER FREE SERVICE					
	ITEMS	SERVICE  DAYS  KM Note-1	1"	2 <sup>nd</sup> Next 100 3000- 3500	3 <sup>rd</sup> Next 100 6000- 6500	4 <sup>th</sup> Next 100 9000- 9500	5 <sup>th</sup> Next 100  12000- 12500	ONCE IN EVERY						
	112.10		1st 60 500- 750											
								3000	6000	9000	12000	15000		
	Battery Voltage		I	I	I	I	I	I						
	Brake Pads Wear		I	I	I	I	I	I						
	Brake Fluid	Note-5	I	I	I	I	I	I						
1	Brake System (Brake Pedal)			I, C, L		I, C, L				I, C, L				
1	Stop Lamp Switch		I, A	I, A	I, A	I, A	I, A	I, A						
1	Headlamp Focus		I, A	I, A	I, A	I, A	I, A	I, A						
	Clutch Lever Free Play		I, A	I, A	I, A	I, A	I, A	I, A						
	Side Stand/ Main Stand (Optional)		L	L	L	L	L	L						
	Side Stand Switch		I, C	I, C	I, C	I, C	I, C	I, C						
•	Nut, Bolts & Fasteners	Note-6	I	I	I	I	I	I						
*	Wheels Bearings	Note-7	I	I	I	I	I	I						
*	Wheel/Tyres		I	I	I	I	I	I						
*	Steering Head Bearing		I	I, A	I	I, A	I, L, A	I	I, A		I, L, A			
×	Front Suspension/Oil	Note-8	I	I	I	I	I	I						
1	Rear Suspension	Note-9	I	I	I	I	I	I						
*	Muffler (Catalytic Converter)	Note-10			I, E		I, E		I, E					
1	Evaporative Emission Control System	Note-11	I	I	I	I	I	I						