



THE ALL NEW
Splunk

NOW WITH **MORE POWER**
THAN EVER



New Graphics
Sporty speed line graphics



New console
with side stand indicators



ATFT Engine
delivering 15.6 BHP



Air filters
New Viscous
Air Filters



**Inverted
GRS suspension**

Contoured Visor | Flared Fender | Tubeless Tyres | Front & Rear Disc Brakes | Ridged Muffler Cover



*Conditions apply.

Accessories and features shown may not be part of standard fitment.



Power Packed Engine Delivering 15.6 BHP

PANTHER BLACK



MATTE BLACK



EBONY GREY



FORCE SILVER



BOLD BROWN



BLAZING RED



ENGINE

Type	Air cooled, 4 - stroke single cylinder OHC
Displacement	149.2 cc
Maximum Power	11.64 KW (15.6 BHP) @ 8500 rpm
Maximum Torque	13.50 Nm @ 7000 rpm
Bore X Stroke	57.3 x 57.8 mm
Compression Ratio	10:1
Carburettor	CV Type with Carburettor Controlled Variable Ignition - Mukini
Starting	Self Start
Ignition	AMI- Advanced Microprocessor Ignition System

TRANSMISSION

Clutch	Multiplate wet
Gear Box	5 Speed constant mesh

CHASSIS

Type	Tubular, Diamond Type
------	-----------------------

SUSPENSION

Front	Telescopic Hydraulic Shock Absorbers
Rear	Rectangular Swing Arm with 5 step adjustable Inverted Gas Reservoir Suspension

BRAKES

Front	DISC – Dia 240 mm
Rear	DRUM – 130 mm Internal expanding shoe type DISC – Dia 220 mm (Optional)

WHEELS AND TYRES

Rim Size	
Front	18 x 1.85, Alloy Wheels
Rear	18 x 2.15, Alloy Wheels
Tyre Size	
Front	80/100 x 18 – 47 P, Tubeless Tyres
Rear	100/90 x 18 – 56 P, Tubeless Tyres

WEIGHTS

Kerb Weight	146 kg (Brakes - FR/RR --> Disc/Drum)
	147 kg (Brakes - FR/RR --> Disc/Disc)
Max. Payload	130 kg

DIMENSIONS

L x W x H	2080 x 765 x 1095
Wheelbase	mm
Ground Clearance	1325 mm 163 mm

ELECTRICALS

Battery	12V – 4 Ah, MF Battery
Head Lamp	12 V – 35 W/ 35 W – Halogen Bulb Trapeziodal MFR
Tail/Stop Lamp	12V – 0.5 W / 4.1 W (LED lamps)
Turn Signal Lamp	12V – 10 W (Amber Bulb) x 4 nos. (Multi – Reflector – Clear Lens)