







SPECIFICATIONS



ENGINE

Air cooled, 4 - stroke single cylinder OHC Type Displacement 97.2 cc 5.74 kW (7.8 Ps) at 7500 rpm Maximum Power 0.82 Kg-m (8.04 N-m) @ 4500 rpm Maximum Torque Bore x Stroke 50.0 x 49.5 mm Side Draft, Variable Venturi Type with TCIS Carburettor DC - Digital CDI Ignition

TRANSMISSION

4 Speed constant mesh Gear box

CHASSIS

Tubular double cradle frame Type

SUSPENSION

Telescopic Hydraulic Shock Absorbers Front Swing Arm with 5 step adjustable hydraulic Rear shock absorber

BRAKES

Disc Disc Brake - Dia 240 mm Front

Internal expanding shoe type (130 mm) Rear Drum

WHEEL AND TYRES

Cast Wheels Rim Size Front 18 x 1.60 Rear 18 x 1.60 Cast Wheels Tyre Size 2.75 x 18 - 6 PR / 50 L Front

3.00 x 18 - 6 PR / 52 P Rear

ELECTRICALS

MF Battery, MF-4:12 V 3 Ah (Self) Battery 12V- 35W / 35W - Halogen Bulb Head Lamp

(Multi-Reflector Type)

12V-5 / 10 W (Multi-Reflector) Tail / Stop Lamp 12V - 10W x 4 nos (Multi-Reflector -Turn Signal Lamp

Clear Lens) Amber Bulb

DIMENSIONS

1980 x 840 x 1085 mm Length x Width x Height Wheelbase 1235 mm

Saddle Height 795 mm Ground clearance 165 mm

WEIGHTS

119 Kg (Self) Kerb weight

12.8 Litre (Min), 1 Litre (Usable Reserve) Fuel Tank Capacity



for better road grip

Bash Plate to Shield Engine









Knee Pad

for better grip





Electric Blue



Sports Red



Black with Sports Red

Hero

SafeTech

Hero **StyleTech**

Hero SafeTech and StyleTech represent our design philosophy for advanced Safety & Styling through cutting-edge Technology and Innovation.



Regd. Office: 34, Community Centre, Basant Lok, Vasant Vihar, New Delhi - 110057. CIN: L35911DL1984PLC017354 For more information, call toll free no.: 1800-266-0018 or

visit heromotocorp.com