I's Hero

HR 98 B 7060

CHALLENGE THE EXTREME THE FASTEST*160CC



*Fastest compared to all oil & air cooled engine motorcycles in the 160cc segment as per internal testing.

WE'RE THE FASTEST

EVERY NUT, EVERY BOLT. EVERY LAP, EVERY RACE. WE SET AN IMPOSSIBLE PACE.

NEVER PAUSING FOR ANYTHING. NEVER COMPROMISING.

WE'RE THE ONES WHO PLAY IT FAST. WE'RE THE ONES WHO OWN THE PLAY.

WE CHALLENGE THE EXTREME.

COMFORTABLE PILLION SEAT

EXTREMELY COMFORTABLE

We're fast. Faster than fast. We know that. You know that. But now, no one gets left behind.

With a flatter profile for improved overall comfort, the pillion rider has easy accessibility and axis, along with an improved position to rear grips, ensuring no compromises for both riders.

LCH D

EXTREMELY SHARP

Your All-Conditions Partner Is Here.

From wet to dry to rough roads.

Make front and rear wheel lock ups a thing of the past.

1st IN SEGMENT PANIC BRAKE ALERT

EXTREMELY RESPONSIBLE

Stay Safe. Always.

The rapid deceleration indicator ensures that not just the rider, but surrounding traffic are safe even in emergency braking situations.



DRAG TIMER

EXTREMELY ON POINT

Make Records. Break Records. Repeat.

With dual mode for acceleration (D1 Mode, O-60km/H) and lap time (D2 Mode, quarter mile timing) both, back up your claims to be the fastest.

KYB USD FORKS

HR 98 B 7060

EXTREMELY AGILE

Fear No Corner.

Ride with the same control as you would on the straights, Thanks to the brilliant 37mm KYB USD Forks.

NEW TAIL LIGHT



THE REPORT

EXTREMELY NEW-AGE

The Fastest Shine Brightest.

The signature 'H' is not only new age, but it also compliments the visual flatness of the bike.

IMPROVED SPEEDOMETER BRIGHTNESS



17 230

EXTREMELY ILLUMINATED

 \bigcirc

0

Ô

T

High Speed Meets High Visibility.

300% improvement in LCD brightness ensures improved readability even under direct sunlight.

EXTREMELY LOADED

IMPROVED SPEEDOMETER BRIGHTNESS

DRAG TIMER



TREME 4

NEW TAIL LIGHT

PANIC BRAKE ALERT

DUAL CHANNEL ABS



THE FASTEST 160CC



SPECIFICATIONS

	SPECS	PRO VARIANT
ENGINE	Engine Type	4 Stroke, Air-Oil Cooled, 4 Valve
	Bore & Stroke	66.5 mm x 47.0 mm
	Displacement (cm ³)	163.2
	Compression Ratio	10.1:1
	Max Power	16.9 Ps/12.4kW @ 8500rpm
	Max Torque	14.6 Nm @ 6500 rpm
	Transmission Type	5 Speed Constant Mesh
	Clutch Type	Multiplate Wet
CHASSIS	Frame Type	Tubular Underbone Diamond Type
	Swing Arm	Box type (50x30mm rectangle tube)
SUSPENSION	Front Suspension Type	KYB USD Forks, 37mm Dia
	Rear Suspension Type	7 Step Adjustable Monoshock
BRAKES	Front Brake type	Disc 276 mm (Petal)
	Rear Brake Type	Disc 220 mm (Petal)
WHEELS & TYRES	Wheel Type	Alloy
	Front Tyre Size	100/80 -17 (TL)
	Rear Tyre Size	130/70 R 17 (TL)
ELECTRICALS	Lamps	LED Headlight with Position Lamp, LED Tail lamp and LED Winkers
	Battery (V-Ah)	12 V-6AH (VRLA)
	Starting System	Self Start
WEIGHT & DIMENSIONS	Overall Length (mm)	2029
	Overall Width (mm)	793
	Overall Height (mm)	1052
	Wheelbase (mm)	1333
	Seat Height (mm)	795
	Ground Clearance (mm)	165
	Fuel Tank Capacity (L)	12

