Hero

INTRODUCING

XTREME 250R

THE FASTEST 250CC#

CHALLENGE THE EXTREME

#Fastest compared to all liquid, air-oil cooled engine motorcycles in the 250cc segment as per internal testing.

THE FASTEST 250CC#

#Fastest compared to all liquid, air-oil cooled engine motorcycles in the 250cc segment as per internal testing.

DOHC 4V LIQUID COOLED ENGINE

(WITH 30PS @ 9250RPM PEAK POWER, 25NM @ 7250RPM PEAK TORQUE)

More power with enhanced cooling for low and mid-range drivability.



RACE READY LAP & DRAG RACE TIMER

Valuable insights that boost speed, efficiency, and consistency in racing environment.

HERO CONNECT (ESIM-BASED) BLUETOOTH CONNECTIVITY

Stay connected with alerts on-the-go.



6-SPEED TRANSMISSION WITH ASSIST & SLIPPER CLUTCH

Smooth shifts with light clutch action for comfort and harnessing maximum performance.



BEST-IN-SEGMENT SWITCHABLE DUAL CHANNEL ABS (WITH REAR WHEEL LIFT-OFF PROTECTION)

Enjoy peak performance while switching effortlessly between road and sports modes.



43MM USD DUAL CARTRIDGE FORKS

Race-bred suspension for high-speed handling and stability.

FASTEST 0-60 KMPH AND 0-100 KMPH

6-STEP ADJUSTABLE MONOSHOCK REAR SUSPENSION

Improved cornering,
ride quality, and traction for
a smoother experience.

TRELLIS FRAME WITH HIGH TORSIONAL STIFFNESS

Lightweight and strong frame for precise control and agile handling.

50-50 WEIGHT BALANCE

Balanced chassis for maximum stability and razor sharp precision.



FIRST-IN-SEGMENT INTELLIGENT ILLUMINATION HEADLAMPS

Headlamps that turn on automatically in dark or low-visibility conditions.

INTRODUCING

XTREME 250R

THE FASTEST 250CC#

SPECIFICATIONS

	Parameter	Specs
Engine	Engine Type	4 Stroke 4 Valve Single Cylinder Liquid Cooled DOHC
	Bore & Stroke	73 mm x 59.5 mm
	Displacement (Cm³)	249.03 cc
	Compression Ratio	12:1
	Max Power (PS/rpm)	30 PS @ 9250rpm
	Max Torque (Nm/rpm)	25 Nm @ 7250 rpm
	Fuel delivery Type	Fuel Injection System, Bosch EFI
Transmission & chassis	Frame Type	Steel Trellis Frame
	Swing Arm	Rectangular Swing arm
	Transmission Type	6-speed, Constant Mesh
	Clutch Type	Wet type-Assist & Slip
Suspension	Front Suspension Type	Dia 43 mm, Upside Down Front Fork
	Rear Suspension Type	Gas Charged Mono Shock, 6 Step Pre-load Adjustable
Brakes	Front Brake type	Disc 320 mm , Petal disc
	Rear Brake Type	Disc 230 mm, Petal Disc
	ABS	Dual Channel Switchable ABS with 2 modes
Wheels & tyres	Wheel Type	Diamond Cut Alloy wheels
	Front Tyre Size	110/70 17 M/C 54H
	Rear Tyre Size	150/60 17 M/C 66W
Electricals	Battery (V-Ah)	MF Battery 12V- 8 Ah, ETZ-9
	Headlamp	Class-D LED Projector Headlamp, with LED DRLs
	Tail Light	Signature H Shaped LED Tail Light
	Winker	LED winkers with Hazard Indicator switch
	Instrument Cluster	LCD
	Starting System	Self
Dimensions	Overall Length	2023 mm
	Overall Width	828 mm
	Overall Height	1062 mm
	Wheelbase	1357 mm
	Seat Height	806 mm
	Ground Clearance	167 mm
	Fuel Tank Capacity	11.5 L
	Kerb Mass	167.7 kg



heromotorcorp.com | Hero MotoCorp | Hero MotoCorp | Hero MotoCorp | Hero MotoCorp

Hero MotoCorp Ltd.

Regd. Office: The Grand Plaza, Plot No. 2, Nelson Mandela Road, Vasant Kunj, Phase - II, New Delhi - 110070, India. CIN: L35911DL1984PLC017354 | For further information, contact your nearest Hero MotoCorp authorised outlet or call our Toll-free no.: 1800 266 0018 or visit us on www.heromotocorp.com.

SCAN QR CODE TO KNOW MORE

INDIA'S FIRST 5 YEAR WARRANTY*

*Conditions apply