



## STYLE AND TECH THAT KEEPS YOU AHEAD



11/4/5/4/125/



## SPECIFICATIONS

Engine	Engine Type	Air cooled A stroke single sylinder OUC
	Engine Type	Air cooled, 4 stroke single cylinder, OHC
	Displacement	124.6 cc
	Maximum Power	6.8 kW (9.1 BHP) @ 7000 rpm
	Maximum Torque	10.22 N-m @ 5000 rpm
	Bore x Stroke	52.4 x 57.8
	Compression Ratio	9.9:1
	Starting	Self/Kick start
	Fuel Supply	FI
Transmission	Clutch	Dry, automatic centrifugal clutch
Chassis	Frame Type	High rigidity under bone type
Suspension	Front	Telescopic, hydraulic shock absorber
	Rear	Unit swing with spring loaded hydraulic damper
Brake	Front	Internal expanding shoe type ( 130 mm ) Disc Dia 190 mm
	Rear	Internal expanding shoe type ( 130 mm )
		Integrated braking system
Tyre Size	Front	90 / 90x12 - 54J (Tubeless)
	Rear	90 / 100x10 - 53J (Tubeless)
Electricals	Battery	12V-4Ah / ETZ-5 *MF Battery
	Headlamp	12V - 35W/35W (Halogen Bulb -MFR*)
	Tail/ Stop Lamp	12V-0.4W / 1.6W x 8 nos. LED
	Turn Signal Lamp	12V - 10W X 4 nos. (Amber bulb) with clear lens
Dimensions	Length	1843 mm
	Width	718 mm
	Height	1188 mm
	Wheelbase	1261 mm
	Ground Clearance	155 mm
Weights	Kerb Weight	110 kg
	Fuel Tank Capacity	5 litres
	ruel latik Capacity	3 littes