



MADE OF TRUST



GLAMOUR

— 125 —

RESTEZ À L'AVANCE



WORLD'S
NO.1
TWO WHEELER COMPANY

GLAMOUR

— 125 —



SPECIFICATIONS

| | | |
|------------------|--|---|
| Engine | Engine Type Displacement Maximum Power Maximum Torque Bore x Stroke Compression Ratio Ignition | Air cooled, 4 – stroke, single cylinder, OHC 124.7 cc 8.3 kW (11 BHP)@7500 rpm 11.0 Nm @ 6000 rpm 52.4 X 57.8 mm 10 : 1 Digital DC CDI ignition system- AMI |
| Transmission | Clutch Transmission | Multi-plate, wet type 4 – Speed constant mesh gear |
| Chassis | Type | Semi Cradle |
| Suspension | Front Rear | Telescopic hydraulic shock absorbers Rectangular swing arm with 5 step adjustable hydraulic shock absorber. |
| Brake | Front Rear | Disc dia. 240 mm Drum- 130mm |
| Wheels and Tyres | Tyre Size Front Rear Headlamp Tail/ Stop Lamp Turn Signal Lamp | 80/100-18, 47P - Tubeless Tyre 90/90-18, 51P - Tubeless Tyre 12V- 35W / 35W (Halogen Bulb –MFR*) LED 12V- 10W X 4 (Amber bulb) With Clear Lens MFR* |
| Dimensions | Length Width Height Wheelbase Ground Clearance | 2023 mm 766 mm 1091 mm 1262 mm 159 mm |
| Weights | Kerb Weight Fuel Tank Capacity Reserve | 127kgs 11 litres 1.4litres |