



SPECIFICATIONS

	Engine Type	Air cooled, 4 stroke single cylinder, OHC
Engine	Displacement	124.6 cc
	Maximum Power	6.5 kW (8.7 BHP) @ 6750 rpm r/min
	Maximum Torque	10.2 N-m @ 5000 rpm r/min
	Bore x Stroke	52.4 x 57.8 mm
	Compression Rat	io 9.9 :1
	Starting	Electric start/Kick start
	Ignition	i3s+TCl unit
Transmission	Clutch	Dry, automatic centrifugal clutch
Chassis	Туре	High rigidity under bone type
6	Front	Telescopic, hydraulic shock absorber
Suspension	Rear	Unit swing with spring loaded hydraulic dampe
	Front	Disc Dia. 190 mm
Brake	Rear	Internal expanding shoe type dia 130 mm (Integrated Braking System)
Tyre Size	Front	90/90 -12 54 J (Tubeless tyre)
1910 3120	Rear	90/100 -10 53 J (Tubeless tyre)
	Headlamp	13.2V-17W/8.5W (LED)
Electricals	Tail/ Stop Lamp	12V - 0.4W/1.6W Qty-8 nos. (LED)
Electricals	Turn Signal Lamp	12V - 10W X 4 nos. (Amber bulb) With Clear Lens **MFR
	Length	1843 mm
	Width	718 mm
Dimensions	Height	1139 mm
	Wheelbase	1261 mm
Weights	Ground Clearance	e 155 mm
	Kerb Weight	112 kg
Weights	Fuel Tank Capacit	ty 5.5 litres
	NEW YORK OF THE PARTY OF THE PA	