



HERO

THE ALL NEW

MAESTRO

EDGE

XTec



 niloyhero.com

Scan To Download
HERO RideGuide
(App for Smart Connectivity)



SPECIFICATIONS

ENGINE

Type	Air cooled, 4 stroke single cylinder, OHC
Displacement	110.9cc
Max Power	5.80 kW @ 7500 Revolution Per Minute (rpm)
Max Torque	8.50 N-m @ 5500 Revolution Per Minute (rpm)
Starting	Electric start/Kick start
Ignition	i3s+TCI unit

TRANSMISSION

Clutch	Dry, automatic centrifugal clutch
Gear Box	Variomatic Drive

SUSPENSION

Front	Telescopic Hydraulic Shock Absorber
Rear	Unit Swing with Spring Loaded Hydraulic Damper

TYRES

Front Tyre	90/90-12 54J (Tubeless tyre)
Rear Tyre	90/100-10 53J (Tubeless tyre)

DIMENSIONS

Length x Width x Height	1843 mm x 715 mm (drum) x 1139 mm
Wheelbase	1261 mm
Seat Height	775 mm
Ground Clearance	155 mm

ELECTRICALS

Battery	12 V - 4 Ah ETZ5 MF Battery
Tail Lamp	12V - 0.4W/1.6W Qty-8 nos. (LED)
Head Lamp	13.2V-17W/8.5W (LED)

WEIGHT

Kerb Weight	110 kg
Maximum Payload	130 kg
Fuel Tank Capacity	5.5 Litres

THE ALL NEW MAESTRO EDGE XTEC

EXCITING FEATURES



AVAILABLE COLOURS



NILOY MOTORS LIMITED

(Sole Distributor of Hero Motorcycle)

Nitol-Niloy Tower, Plot-69, Nikunja-2 C/A, Khilkhet, Dhaka-1229, Bangladesh.
E-mail: corporate@niloymotors.com | Phone: 09636 666 666

HMCL NILOY BANGLADESH LIMITED

(Joint Venture of Hero Moto Corp Ltd, India & Niloy Motors Ltd. Bangladesh)

Nitol-Niloy Tower, Plot-69, Nikunja-2 C/A, Khilkhet, Dhaka-1229, Bangladesh.
www.heromotocorp.com/bd

