



# Splendor+ XTEC



TUBELESS  
TYRES



NOW WITH **SMART CONNECTIVITY**

**1<sup>ST</sup>**  
**IN**  
**SEGMENT**

**CALL & SMS ALERT**



DIGITAL METER  
CONSOLE WITH XTEC



EXCITING BODY  
GRAPHICS



3D LOGO BADGING



DAYTIME RUNNING  
LIGHT (DRL)



USB CHARGING PORT

Scan To Download

**HERO RideGuide**  
(App for Bluetooth Connection)



## SPECIFICATIONS

### ENGINE

Type	Air cooled, 4 - Stroke Single Cylinder OHC
Displacement	97.2 cc
Maximum Power	6.15 kW (8.36 Ps) @ 8000 Revolutions per minute
Maximum Torque	0.82 Kgfm (8.04 N-m) @ 5000 Revolutions per minute
Compression Ratio	9.9:1
Starting Ignition	Self Start (with i3S) & Kick DC - Digital CDI

### TRANSMISSION

Clutch	Multiplate Wet
Gear box	4 Speed Constant Mesh

### CHASSIS

Type	Tubular Double Cradle Type
------	----------------------------

### SUSPENSION

Front	Telescopic Hydraulic Shock Absorbers
Rear	Swing Arm with 5 Step Adjustable Hydraulic Shock Absorber

### WHEELS AND TYRES

Tyre	Front	80/100-18 M/C 47P (Tubeless)
	Rear	80/100-18 M/C 54P (Tubeless)
Brakes	Front	Internal Expanding Shoe Type (130 mm) - Non Asbestos type
	Rear	Internal Expanding Shoe Type (130 mm) - Non Asbestos type

### ELECTRICALS

Battery	12V-3 Ah MF (ETZ4)
Head Lamp	12 V - 35/35 W - Halogen Bulb (MFR)
Tail Lamp	12 V -5 / 10W (Multi-Focal Reflector)

### DIMENSIONS

Length	2000 mm
Width	720 mm
Height	1040 mm
Wheelbase	1230 mm
Ground clearance	159 mm

### WEIGHTS

Kerb weight	112.3 kgs (Electric Start)
Max. Payload	130 kgs

### CAPACITY

Fuel Tank Capacity	11 Litre
Reserve	1.1 Litre (Usable Reserve)



**GOLD BLACK**



TUBELESS TYRES



### NILOY MOTORS LIMITED

(Sole Distributor of Hero Motorcycle)

Nitol-Niloy Tower, Plot-69, Nikunja-2 C/A, Khilkhet, Dhaka-1229, Bangladesh.  
E-mail: corporate@niloymotors.com | Phone: 09636 666 666

### HMCL NILOY BANGLADESH LIMITED

(Joint Venture of Hero Moto Corp Ltd, India & Niloy Motors Ltd. Bangladesh)

Nitol-Niloy Tower, Plot-69, Nikunja-2 C/A, Khilkhet, Dhaka-1229, Bangladesh.  
www.heromotocorp.com/bd



\*Conditions apply.