


# RELE A FOUR VALVE

=THE FASTEST\* 160CC=



EVERY DRAGSTER'S DREAM





change. Xtreme 160R 4V's fastest acceleration will get you high on thrill and make objects in the rearview mirror disappear in a flash.

4-valve technology & best-in-class 5 Fin Oil Cooler deliver next level performance while maintaining thermal stability and engine refinement.

FOUR VALVE

### THE FASTEST\* 160CC-

Fastest 0-60 | Fastest 0-100 | Fastest 0-Top Speed | Fastest in Drag Race

# RIDE EASY RACE HARD



KYB USD Forks
37mm Dia for a
macho stance.

### Bluetooth Connectivity

Never miss a call or text alert.





### Inverted LCD Display

Be it bright or dark. For you, it'll be perfect.









All LED Lights
Light up the road for your fellow dragsters.

# THE BEST SINON BETTER



Mono Shock Suspension 7 step adjustable, for pre-load.

130mm Radial Rear Tyre

Better stability, better grip.

# BRAG WOURS

CHOOSE FROM AN EXCITING RANGE OF COLOURS, AND LET THE RACE BEGIN.

Neon Shooting Star
Pro variant

Blazing Sports Red Standard variant Matte Slate Black Connect 2.0\* Standard/Connect Variant



# STAY CONNECTED AS YOUR RACE!

00 - 00

## Hero CONNECT

2.0



### LIVE TRACKING

Wander, but don't get lost.



### REMOTE IMMOBILIZATION

Someone else on your seat? Not anymore.



### **VEHICLE DIAGNOSTIC**

Before you race, have it all in place.



#### FIND MY BIKE

Let your phone spot your dragging partner.



#### PANIC ALERT

Help is just a click away.

+20 More Features





## -THE FASTEST\* 160CC-

**SPECIFICATIONS** 

	SPECS	STANDARD VARIANT	PRO VARIANT
ENGINE	Engine Type	4 Stroke, Air-Oil Cooled, 4 Valve	4 Stroke, Air-Oil Cooled, 4 Valve
	Bore & Stroke	66.5 mm x 47.0 mm	66.5 mm x 47.0 mm
	Displacement (cm³)	163.2	163.2
	Compression Ratio	10.1:1	10.1:1
	Max Power	16.9 Ps/12.4kW @ 8500rpm	16.9 Ps/12.4kW @ 8500rpm
	Max Torque	14.6 Nm @6500 rpm	14.6 Nm @6500 rpm
	Transmission Type	5 Speed Constant Mesh	5 Speed Constant Mesh
	Clutch Type	Multiplate Wet	Multiplate Wet
CHASSIS	Frame Type	Tubular Underbone Diamond Type	Tubular Underbone Diamond Type
	Swing Arm	Box type (50x30mm rectangle tube)	Box type (50x30mm rectangle tube
SUSPENSION	Front Suspension Type	Standard Telescopic, 37mm Dia	KYB USD Forks, 37mm Dia
	Rear Suspension Type	7 Step Adjustable Monoshock	7 Step Adjustable Monoshock
BRAKES	Front Brake type	Disc 276 mm (Petal)	Disc 276 mm (Petal)
	Rear Brake Type	Disc 220 mm (Petal)	Disc 220 mm (Petal)
WHEELS & TYRES	Wheel Type	Alloy	Alloy
	Front Tyre Size	100/80 -17 (TL)	100/80 -17 (TL)
	Rear Tyre Size	130/70 R 17 (TL)	130/70 R 17 (TL)
ELECTRICALS	Lamps	LED Headlight with Position Lamp, LED Tail lamp and LED Winkers	LED Headlight with Position Lamp, LED Tail lamp and LED Winkers
	Battery (V-Ah)	12 V-6AH (VRLA)	12 V-6AH (VRLA)
	Starting System	Self Start	Self Start
WEIGHT & DIMENSIONS	Overall Length (mm)	2029	2029
	Overall Width (mm)	793	793
	Overall Height (mm)	1052	1052
	Wheelbase (mm)	1333	1333
	Seat Height (mm)	795	795
	Ground Clearance (mm)	165	165
	Fuel Tank Capacity (L)	12	12
	Kerb Weight (kg)	144	145

Connected 2.0 Features available as a variant over Standard

EVERY DRAGSTER'S DREAM