



PRESENTING
HF-Deluxe



POWERFUL
HEADLAMP



SELF START



SIDE STAND
INDICATOR



HF-Deluxe

TECHNICAL SPECIFICATIONS

Engine	Type	Air cooled, 4 stroke single cylinder, OHC
	Displacement	97.2 cc
	Maximum Power	6.15 kw , (8.36ps) @ 8000 rpm
	Torque	0.82 kgfm (8.05 N-m) @ 5000 rpm
	Compression Ratio	9.9:1
	Starting	Self Start
	Ignition System	Digital DC CDI
Transmission	Clutch	Multi-plate, wet type
	Transmission	4 -speed constant mesh gear
Chassis	Type	Tubular double cradle
Suspension	Front Suspension	Telescopic hydraulic shock absorbers
	Rear Suspension	Swing arm with 2 step adjustable hydraulic shock absorbers
Tyres	Front Tyre Size	80/100 – 18M/C 47P (Tubeless Tyres)
	Rear Tyre Size	80/100 – 18M/C 54P (Tubeless Tyres)
Brakes	Front Brake	Internal expanding shoe type dia 130 mm
	Rear Brake	Internal expanding shoe type dia 110 mm
Electrical	Battery	12V – 3Ah ETZ-4 MF Battery
	Head Lamp (High/Low)	12V- 35W / 35W (Halogen Bulb –MFR **)
	Tail / Stop Lamp	12V – 5W / 21W MFR**
Dimensions	Overall Length	1965 mm
	Overall Width	720 mm
	Overall Height	1045 mm
	Wheelbase	1235 mm
	Ground Clearance	165 mm
Weights	Kerb Weight	110 kg
	Maximum Payload	130 Kg
Capacity	Fuel Tank Capacity	9.5 Litres (1.5 Litres usable reserve)