



XOM 125R

—BUILT TO
OUTPERFORM



TECHNICAL SPECIFICATIONS

Engine	Type	Air Cooled, 4 Stroke, SI Engine
	Displacement	124.6 cc
	Max Power	7.3 kw (9.8 bhp) @ 7250 rpm
	Max Torque	10.4 Nm @ 6000 rpm
	Ignition	Fuel Injection (FI))
Transmission	Type	CVT
	Clutch Type	Dry, Centrifugal
Suspension	Front	Telescopic Hydraulic Shock Absorber
	Rear	Single Side Shock Absorber
Tyres	Front	110/80 - [R 14]
	Rear	120/70 - [R 14]
Dimensions	Length	1978 mm
	Width	Disc - 749 mm
	Height	1131 mm
	Wheelbase	1327 mm
	Seat Height	777 mm
	Ground Clearance	164 mm
Electricals	Battery	12V- 4Ah /ETZ-5
	Starting System	Electric/kick start
Weight	Kerb Weight	Disc - 121 kg
	Fuel Tank Capacity	5 L

COLOURS



MATT
GIALLO LIME



MATTE
NEXUS BLUE



CANDY
BLAZING RED



MAT AXIS
GRAY METALLIC

PERFORMANCE



FASTEST 125CC SCOOTER



i3s TECHNOLOGY



**LED PROJECTOR
HEADLAMP**



**FRONT
DISC BRAKES**

ULTIMATE COMFORT



**[R 14]
LARGE WHEELS**



**120 MM
WIDE REAR TYRE**



**REMOTE
FUEL LID OPENING**



**DIGITAL
SPEEDOMETER**

SIGNATURE STYLE



**FALCON INSPIRED
POSITION LIGHT**



**SEQUENTIAL LED WINKERS
1ST IN SEGMENT



**ILLUMINATED
START SWITCH**

*Fastest compared to all scooter models in the 125cc segment as per internal testing

**Internal benchmarking on basis of data available in public forum for 125cc segment scooters in Nepal