

## SPECIFICATIONS

	Overall length	2222
Dimensions	Overall width	862
	Overall height	1320
	Wheelbase	1410
	Seat height	825
	Ground clearance	220
	Kerb weight (kg)	159 kg
Frame	Frame type	Diamond type
	Front suspension	Telescopic Front Forks (dia 37) with anti friction bush
	Rear suspension	Rectangular swingarm with 10 step preload adjustable mono shock
	Front tyre size	90/90-21 M/C 54S
	Rear tyre size	120/80-18 M/C 62S
	Front brake   Disc type	Petal Disc Dia. 276 mm
	Rear brake   Disc type	Petal Disc Dia. 220 mm
	Fuel tank capacity	13.0 Litres
Engine	Туре	Oil cooled, 4-stroke, 4 valve single cylinder OHC
	Maximum power	14.1 kW/ 18.9 BHP @ 8500 RPM
	Maximum torque	17.35 Nm @ 6500 rpm
	Bore and stroke	66.5mm X 57.5mm
	Displacement	199.6cc
	Compression ratio	10.5:1
Drive train	Clutch system	Multi-plate, wet type
	Transmission	5-speed constant mesh
	Starting	Self and Kick
	Battery capacity	12V- 6 Ah, ETZ-7 *MF Battery
Lamps	Headlamp	LED (Class D with DRL)
	Tail light	LED
	Instrument cluster	Full digital LCD, with Bluetooth  & Turn by Turn navigation

AVAILABLE COLOURS

Matte Nexus Blue

**Black Sports Red** 

Techno Blue











BORN FOR THE TOUGHEST TERRAINS





HANDLEBAR RISER



**EXTENDED GEAR LEVER** 



INCREASED GROUND CLEARANCE OF 270 MM



ADJUSTABLE FRONT SUSPENSION OF 250 MM



ADJUSTABLE REAR SUSPENSION OF 220 MM



## SPECIFICATIONS

	Items	Pro Variant
Dimensions	Overall Length	2255 mm
	Overall Width	862 mm
	Overall Height	1380 mm
	Wheelbase	1427 mm
	Seat Height	891 mm
	Ground Clearance	270 mm
	Kerb Weight	161 kg
Frame	Frame Type	Diamond Type
	Front Suspension	Cartridge Type (Dia. 37 mm) with Adjustable Compression & Rebound Damping
	Rear Suspension	Rectangular Swingarm with 10-step Preload Adjustable Mono Shock
	Front Tyre Size	90/90-21 M/C 54S
	Rear Tyre Size	120/80-18 M/C 62S
	Front Brake   Disc Type	Petal Disc Dia. 276 mm
	Rear Brake   Disc Type	Petal Disc Dia. 220 mm
	Fuel Tank Capacity	13.0 Litres
Engine	Type	Oil-cooled, 4-Stroke, 4-Valve Single Cylinder OHC
	Maximum Power	14.1 kW/ 18.9 BHP @ 8500 RPM
	Maximum Torque	17.35 Nm @ 6500 RPM
	Bore and Stroke	66.5 mm X 57.5 mm
	Displacement	199.6cc
	Compression Ratio	10.5:1
Drive train	Clutch System	Multi-plate, Wet Type
	Transmission	5-speed Constant Mesh
	Starting	Self and Kick
	Battery Capacity	12V- 6 Ah, ETZ-7 *MF Battery
Lamps	Headlamp	LED (Class D with DRL)
	Tail Light	LED
	Instrument Cluster	Full digital LCD, with Bluetooth & Turn-by-turn Navigation

