



INTRODUCING
THE POWERFUL NEW
DAWN-150

5 GEARS



DAWN-150

SPECIFICATIONS

ENGINE

Type	Air Cooled, 4-Stroke Single Cylinder OHC
Displacement	149.1 cc
Cylinder Arrangement	One Cylinder, Vertical Engine
Maximum Power	10 kW(13.4 bhp) @8000 rpm
Maximum Torque	12.80 N-m @5000 rpm
Bore X Stroke	57.3 X 57.8 mm
Compression Ratio	9.1 :1
Starting	Self Start/ Kick Start
Ignition	Ami- Advanced Microprocessor ignition System

TRANSMISSION

Clutch	Multiplate Wet
Gear Box	5 Speed Constant Mesh

CHASSIS

Type	Tubular, Diamond Type
------	-----------------------

SUSPENSION

Front	Telescopic Hydraulic Shock Absorbers
Rear	Swing Arm With Adjustable Hydarulic Shock Absorber

BRAKES

Drum	Front	Internal Expanding Shoe Type (130)mm- Non Asbestoes Type
Drum	Rear	Internal Expanding Shoe Type (130)mm- Non Asbestoes Type

WHEELS & TYRES

Rim Size	Front	18 X 1.60, Cast Wheel & Spoke
	Rear	18 X 1.60, Cast Wheel & Spoke

SPECIFICATIONS

TYRE SIZE

Front	2.75 X 18 - 42 P / 4 PR
Rear	3.00 X 18 - 52 P / 6 PR

ELECTRICALS

Battery	12v - 4 Ah, MF Battery
Head Lamp	35W/35W - Halogen Bulb (Round Shape)
Tail/stop Lamp	5/21 W (Multi - Reflector)
Turn Signal Lamp	10 W X 4 Nos (Multi - Reflector)

DIMENSIONS

Length	2061 mm
Width	763 mm
Height	1100 mm
Wheelbase	1290 mm
Ground Clearance	160 mm

WEIGHTS

Kerb Weight	140 Kg Self
-------------	-------------

• It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice.

Authorized Distributor:

Authorized Dealer of Distributor:



GENUINE PARTS

Accessories and features shown may not be part of standard fitment. Always wear a helmet while riding a two wheeler.

Regd. Office: Hero MotoCorp Ltd., 34, Community Centre, Basant Lok, Vasant Vihar, New Delhi - 110057. For further information, contact nearest Hero MotoCorp authorised outlet or visit www.heromotocorp.com.