



Hunk

BECAUSE MUSCLES MATTER



New Graphics
Fiery pyroclastic
graphics



New Console
with side stand
indicators



ATFT Engine



Inverted
GRS suspension


PANTHER BLACK

MATTE BLACK

BOLD BROWN

BLAZING RED

ENGINE

Type	Air cooled, 4 - stroke single cylinder OHC
Displacement	149.2 cc
Maximum Power	10.6 KW (14.4 Ps) @ 8500 rpm
Maximum Torque	12.80 Nm @ 6500 rpm
Acceleration	0-60 kmph in 5 sec
Starting	Self Start/Kick Start
Ignition	AMI- Advanced Microprocessor Ignition System

TRANSMISSION

Clutch	Multiplate wet
Gear Box	5 Speed constant mesh

CHASSIS

Type	Tubular, Diamond Type
------	-----------------------

SUSPENSION

Front	Telescopic Hydraulic Shock Absorbers
Rear	Rectangular Swing Arm with 5 step adjustable Inverted Gas Reservoir Suspension

BRAKES

Front	DISC – Dia 240 mm
Rear	DRUM – 130 mm Internal expanding shoe type DISC – Dia 220 mm (Optional)

WHEELS AND TYRES

Rim Size	
Front	18 x 1.85, Alloy Wheels
Rear	18 x 2.15, Alloy Wheels
Tyre Size	
Front	80/100 x 18 – 47 P, Tubeless Tyres
Rear	100/90 x 18 – 56 P, Tubeless Tyres

WEIGHTS

Kerb Weight	145 kg (Brakes - FR/RR --> Disc/Drum)
	147 kg (Brakes - FR/RR --> Disc/Disc)
Max. Payload	130 kg

DIMENSIONS

Length	2080 mm
Width	765 mm
Height	1095 mm
Wheelbase	1325 mm
Ground Clearance	163 mm

ELECTRICALS

Battery	12V – 4 Ah, MF Battery
Head Lamp	12 V – 35 W/ 35 W – Halogen Bulb Trapeziodal MFR
Tail/Stop Lamp	12V – 0.5 W / 4.1 W (LED lamps)
Turn Signal Lamp	12V – 10 W (Amber Bulb) x 4 nos. (Multi – Reflector – Clear Lens)

Hero MotoCorp Ltd.,

Registered Office: 34, Community Centre, Basant Lok, Vasant Vihar, New Delhi – 110057, India. CIN: L35911DL1984PLC017354
Website: www.heromotocorp.com

Accessories and features shown may not be a part of the standard fitment. It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice. Always wear a helmet while riding a two wheeler.