



HF KI MAZBOOTI

IBS KA BHAROSA

Pesh hai nayi ***HF Deluxe, Integrated Braking System*** ke saath.



SPECIFICATIONS

Engine	Type	Air Cooled, 4 Stroke Single Cylinder, OHC
	Power	6.15 kW @ 8000 Revolutions Per Minute (rpm)
	Maximum Torque Value	8.05 Nm @ 5000 Revolutions Per Minute (rpm)
	Displacement	97.2 cc
	Compression Ratio	9.9: 1
Transmission	Clutch System	Multi-Plate, Wet Type
	Transmission	4-Speed Constant Mesh
Chassis	Frame Type	Tubular Double Cradle
Suspension	Front Suspension	Telescopic Hydraulic Shock Absorbers
	Rear Suspension	Swing Arm with 2 Step Adjustable Hydraulic Shock Absorbers
Brakes	Front	Drum 130 mm
	Rear IBS	Drum 130 mm
Tyres	Front Tyre	2.75 x 18 - 4 PR / 42 P
	Rear Tyre	2.75 x 18 - 6 PR / 48 P
Electrical System	Battery	MF Battery, MF- 3: 12 V – 3Ah (Kick Start) MF- 4:12 V – 3Ah (Electric Start)
Weights	Kerb Weight-Kick spoke	109 Kgs
	Kerb Weight-Kick cast	110 Kgs
	Kerb Weight-Self Cast	111 Kgs
	Kerb Weight-Self cast i3S	112 Kgs
	Max. Payload	130 Kgs
Capacity	Fuel Tank Capacity	9.5 Litre
	Reserve	1.4 Litre
Dimension	Length	1965 mm
	Width	720 mm
	Height	1045 mm
	Wheelbase	1235 mm
	Ground Clearance	165 mm
Lamps	Head Lamp	12 V - 35 / 35 W (Halogen Bulb), Trapezoidal MFR
	Tail/Stop Lamp	12 V - 5 / 21 W - MFR

