

# GLAMOUR

— STAND OUT, STAY AHEAD —




# SPECIFICATIONS



ENGINE	
Type	Air cooled, 4 - stroke single cylinder OHC
Displacement	124.7 cc
Maximum Power	6.72 kW (9.1 Ps) @7000 rpm
Maximum Torque	10.35 N-m @4000 rpm
Bore x Stroke	52.4 x 57.8 mm
Compression Ratio	9.1:1
Starting	Self Start / Kick Start
Ignition	AMI - Advanced Microprocessor Ignition System
TRANSMISSION	
Clutch	Multiplate wet
Gear box	4 - speed constant mesh
Chassis Type	Tubular Double Cradle Type
SUSPENSION	
Front	Telescopic Hydraulic Shock Absorbers
Rear	Swing Arm with Hydraulic Shock Absorbers
BRAKES	
Front	Disc
	Drum
Rear	Drum
	Drum
TYRES	
Tyre	Front 2.75 x 18 - 42 P / 4 PR Rear 3.00 x 18 - 52 P / 6 PR

ELECTRICALS	
Battery	12 V - 3 Ah MF Battery
Head Lamp	12 V - 35 W / 35 W - Halogen Bulb (Multi-Reflector Type)
Tail / Stop Lamp	12 V - 5 / 21 W (Multi-Reflector)
Turn Signal Lamp	12 V - 10 W (Amber Bulb) x 4 nos (MFR - Clear Lens)
Engine Oil Grade	SAE 10 W 30 SJ Grade
Fuel Tank Capacity	13 litre (Min)
Reserve	1.4 litre (Usable Reserve)
DIMENSIONS	
LxWxH	2005 mm X 735 mm X 1070 mm
Wheelbase	1265 mm
Ground clearance	150 mm
WEIGHT	
Kerb weight	Self Drum 123 Kg Self Disc 125 Kg

# FEATURES



Digital Silver



Black with Techno Blue



Black with Tornado Grey Metallic



Black with Sports Red



Candy Blazing Red

Hero Glamour Complies with BS-IV emission norms.

Regd. Office: Hero MotoCorp Ltd., 34, Community Centre, Basant Lok, Vasant Vihar, New Delhi - 110057, India. CIN: L35911DL1984PLC017354. Accessories and features shown may not be part of standard fitment. Always wear a helmet while riding a two wheeler. For further information, visit [www.heromotocorp.com](http://www.heromotocorp.com). \*As per SIAM's dispatch numbers for the period April 2016 - January 2017.

# GLAMOUR



\*Conditions apply.