

TECHNICAL SPECIFICATIONS

ELAI IILAL	SPECIFICATIONS
ENGINE_	
Type Bore & Stroke (mm) Displacement (Cm³) Compression Ratio Max Power BHP (kw/rpm) Max Torque (Nm/rpm) Ignition	Air cooled, 4 - stroke single cylinder, OHC 52.4 x 57.8 mm 124.7 cc 10:01 8.3 kW (11.1 bhp) @ 7500 RPM 11 Nm @ 6500 RPM Digital DC CDI Ignition System - AMI
TRANSMISSION	
Clutch Type Gear Box	Multi-Plate Wet Clutch 4-Speed Constant Mesh
CHASSIS	
Туре	Tubular Double Cradle
SUSPENSION	T. L. Sa Hadaradia Charla Abaraham
Front Rear	Telescopic Hydraulic Shock Absorbers 5-Step Adjustable Hydraulic Shock Absorbers
TYRES	
Tyre Front Rear Brake Front Rear	80/100-18M/C 47P Tubeless 80/100-18M/C 54P Tubeless Drum (130 mm) Drum (130 mm)
ELECTRICALS	
Battery Head Lamp Tail / Stop Lamp	12 V - 3Ah MF 12 V - 35 W / 35 W- Halogen Bulb (Multi Reflector Type) 12 V-5 / 21 W (Multi Reflector Type)
DIMENSIONS	
Length Width Height Saddle Height Wheel Base Ground Clearence Fuel Tank Capacity Kerb Weight (kg)	2008mm 740mm 1080mm 790mm 1261.8mm 161.7mm 13 L





Presenting the new Super Splendor with a powerful and high-performance 125cc Engine, __ i3s Technology, and IBS for added safety. A ride that reflects your stature.





