

SPECIFICATIONS

ENGINE

Air - Cooled, 4 - Stroke Single Cylinder OHC Type

Displacement

Maximum Power 6 kW (8 BHP) @ 7500 Revolutions per minute (rpm) Maximum Torque 8.7 Nm @ 5500 Revolutions per minute (rpm)

Starting Self-Start

TRANSMISSION

Clutch **Automatic Clutch**

Gear Box Variomatic Drive (2.51 - 0.85)

SUSPENSION

Front Telescopic, Hydraulic Shock Absorber

Rear Unit Swing with Spring Loaded Hydraulic Damper

DIMENSIONS

Lenath 1841 mm Width 695 mm 1190 mm Height Wheelbase 1261 mm **Ground Clearance** 155 mm

ELECTRICALS

12 V - 4 Ah (MF Battery) Battery 12 V - 0.4/1.6 W - (LED Type) Tail Lamp

Head Lamp 12 V - 35 W/35 W - Halogen Bulb (Multi - Reflector Type)

Turn Signal Lamp 12 V - 10 W x 4 nos (MFR - Clear Lens - Amber Bulb Type)

TYRES

Front 90/90 -12 - 54 J Rear 90/100 - 10 - 53 J

WEIGHT

Kerb Weight 110 Kg Maximum Payload 130 Ka

OPTIONAL ACCESSORIES

- Side Stand
- Side Stand Indicator
- Glove Box

This product is BS-IV compliant



Authorized Outlet



Regd. Office: Hero MotoCorp Ltd. The Grand Plaza, Plot No.2, Nelson Mandela Road, Vasant Kunj - Phase - II, New Delhi - 110070, India. CIN: L35911DL1984PLC017354.

COLOURS HATKE



Active Matte Grey & Blue



Sporty Matte Grey & Red



Shooting Night Star



Panther Black



Pearl Silver White



Candy Blazing Red



Techno Blue



Matte Vernier Grey



Matte Blue

BOLD RIDE, EXCITING FEATURES



ADVANCED /→Xtra Power Delivery ___Xtra Pick-up



TELESCOPIC FRONT SUSPENSION



EXTERNAL FUEL FILLING



BRAKING



PORT



BIGGER FRONT WHEEL & TUBELESS TYRES

It is our endeavour to constantly improve our product. This could lead to changes in product specifications without notice. Accessories and features shown may not be part of the standard fitment. Always wear a helment while riding a two-wheeler. For further information, contact nearest Hero MotoCorp's authorized outlet(s) or call Toll Free No.: 1800-266-0018 or visit website www.heromotocorp.com

