

SPECIFICATIONS		100 1/4 5/4
MODEL	Fi VARIANT	i3S VARIANT
ENGINE	Air Cooled 4 Strake	Cingle Culinder OLIC
Engine Type	Air Cooled, 4-Stroke Single Cylinder OHC	
Displacement	124.6cc	
Max Power	6.8 kW (9.1 BHP) @ 7000	6.5 kW (8.7 BHP) @ 6750
		Revolutions Per Minute (rpm)
Max Torque	10.2 Nm @ 5000 Revolutions Per Minute (rpm)	
Fuel System	Fuel Injection	Carburetor
Starting	Self-Start / Kick-Start	
Ignition	Electronic Control Unit (ECU)	Digital TCI Ignition System (TCI)
TRANSMISSION		
Clutch	Dry, Centrifugal	
Gear Box	Variomatic Drive	
SUSPENSION		
Front	Telescopic Fork	
Rear	Single Coil Spring Hydraulic Type	
BRAKES		
Front Brake Type	Disc Brake 190 mm	Drum Brake 130 mm / Disc Brake 190 mm
Rear Brake Type	Drum Brake 130 mm	
TYRES		
Front Tyre	90/90-12	
Rear Tyre	90/100-10	
ELECTRICALS		
Battery (V-Ah)	12V-4Ah ETZ	-5 MF-Battery
DIMENSIONS		
Length x Width x Height	1843 mm X 718 mm X 1188 mm	
Wheelbase	1261 mm	
Seat Height	775 mm	
Ground Clearance	155 mm	
WEIGHT	100	
Kerb Weight	110 kg	Drum: 109 kg / Disc 110 kg
Maximum Payload	130 kg	
Fuel Tank Capacity	5.0 L 5.5 L	
		J.J L
OPTIONAL ACCESSORI	ES	

FEATURES





COLOURS







i3S Variants





Regd. Office: Hero MotoCorp Ltd. The Grand Plaza, Plot No.2, Nelson Mandela Road, Vasant Kunj - Phase - II, New Delhi - 110070, India. CIN: 135911DL1984PLC017354



Authorized Outlet

It is our endeavour to constantly improve our product. This could lead to changes in product specifications without notice. Accessories and features shown may not be part of the standard fitment. Always wear a helmet while riding a two-wheeler. For further information, contact nearest Hero MotoCorp's authorized outlet(s) or call Toll Free No.: 1800-266-0018 or visit website www.heromotocorp.com.