



NAYI HF DELUXE
AB **i3s** TECHNOLOGY
KE SAATH BHI



STOPS WHEN IDLE*



RESTARTS INSTANTLY**



SAVES PETROL

*Gear in neutral position, crank rotation upto 2000 revolutions per minute (rpm), irrespective of speed.
**Restarts with the press of the clutch.

HF-*Deluxe*
Naye Indian Ka Mazboot Saathi

SPECIFICATIONS

ENGINE

Type	Air Cooled, 4 - Stroke Single Cylinder OHC
Displacement	97.2cc
Maximum Power	6.15 kW (8.36 Ps) @8000 revolutions per minute (rpm)
Maximum Torque	0.82 Kg-m (8.05 N-m) @5000 revolutions per minute (rpm)
Bore x Stroke	50.0 mm x 49.5 mm
Compression Ratio	9.9 : 1
Starting	Kick / Self Start
Ignition	DC - Digital CDI

TRANSMISSION

Clutch	Multiplate Wet
Gear Box	4 Speed Constant Mesh

CHASSIS

Type	Tubular Double Cradle
------	-----------------------

SUSPENSION

Front	Telescopic Hydraulic Shock Absorbers
Rear	Swing Arm with 2 Step Adjustable Hydraulic Shock Absorber

BRAKES

Front	Internal Expanding Shoe Type - (130 mm)
Rear	Internal Expanding Shoe Type - (110 mm)

TYRES

Size	Front	2.75 x 18 - 4 PR / 42 P
	Rear	2.75 x 18 - 6 PR / 48 P

ELECTRICALS

Battery	12 V - 3 Ah (MF Battery)
Head Lamp	12 V - 35 / 35 W (Halogen Bulb), Trapezoidal MFR
Tail / Stop Lamp	12 V - 5 / 21 W - MFR
Turn Signal Lamps	12 V - 10 W x 4 nos - MFR

DIMENSIONS

Length	1965 mm
Width	720 mm
Height	1045 mm
Wheelbase	1235 mm
Ground Clearance	165 mm

WEIGHT

Kerb Weight	107 Kg (Kick) / 110 Kg (Self)
-------------	-------------------------------

CAPACITY

Fuel Tank Capacity (Min)	9.5 Litre
Reserve (Usable)	1.5 Litre

Also available in the following colours:



Black with Red



Black with Blue



Black with Purple



Convenient Power Start



Automatic Headlamp On



Superior Mileage Engine



Stylish Graphics



Also available in standard variant

HF-Deluxe

Naye Indian Ka Mazboot Saathi

