





AN ALL-NEW RANGE OF EXCITING COLOURS











SPECIFICATIONS

Engine Air-cooled, 4-stroke Single Cylinder OHC

Bore x Stroke 50.0 mm x 52.0 mm

Displacement 102cc Compression Ratio 9.9:1

Maximum Power 5.15 kW (6.9 BHP) @ 7000 Revolutions Per Minute (RPM)

Maximum Torque 8.1 Nm @ 5000 Revolutions Per Minute (RPM)

Maximum Speed 77 km/h

Clutch Dry, Automatic Centrifugal Clutch

Ignition C D I Starting Self-start

Front Suspension Bottom Link with Spring-loaded

Hydraulic Damper

Rear Suspension Unit Swing with Spring-loaded

Hydraulic Damper

Length x Width x Height 1750 mm x 705 mm x 1115 mm

Wheel Base 1240 mm Ground Clearance 125 mm Kerb Weight 101 kg

Tyres Front 90/100 x 10 - 53 J

Rear 90/100 x 10 - 53 J

Front Brake Internal Expanding Shoe Type (130 mm)
Rear Brake Internal Expanding Shoe Type (130 mm)

Integrated Braking System (IBS)

Fuel Tank Capacity 5 Litre (Min)

Head Lamp 12 V - 35 W / 35 W - Halogen Bulb

(Multi-Reflector Type)

Position Lamp 12 V - 5 W X 2 Nos-

Battery 12 V - 4.Ah MF Type (Maintenance Free)

This product is BS-IV compliant.





Regd Office: Here MotoCorp Ltd., 34, Community Centre, Basant Lok, Vasant Vihar, New Delhi - 110057, India. CIN: L35911DL1884PLC017354 Authorised Outlet

It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice. Accessories and features shown may not be a part of the standard fitment. Always wear a helmet while riding a two wheeler. Warranty valid for a period of 5 years or 50,000 kms from the date of purchase, whichever is earlier. Visit www.heromotocorp.com