









STYLISH UPSWEPT EXHAUST



TURN BY TURN
NAVIGATION



USB CHARGER



10 Step Adjustable Monoshock

SPECIFICATIONS

ENGINI

Displacement

Bore x Stroke

Starting

Maximum Power

Maximum Torque

Compression Ratio

Engine Type Air cooled, 4 Stroke 2 Valve

Single cylinder, OHC

199.6 cc

13.5kw/18.1 bhp @ 8000 rpm

17.1 Nm @ 6500 rpm 66.5mm X 57.5mm

00.5HIIII X 57.5

10 : 01

Electric and Kick

Fuel Supply

TRANSMISSION & CHASSIS

Frame Diamond
Clutch Muli-plate

Clutch Muli-plate wet clutch
Transmission 5-speed constant mesh gear

FL

SUSPENSION

Front Telescopic front forks (37mm

Dia) with antifriction bush

Rear Rectangular swingarm with

adjustable mono-shock

BRAKES

Front Disc Dia. 276 mm

Rear Disc Dia. 220 mm

WHEELS & TYRES

Front 90/90-21 M/C 54S

Rear 120/80-18 M/C 62S

ELECTRICALS

Battery 12V-6 Ah, (ETZ-7) MF Battery

Headlamp 12V-5.6W/9.3W (LED)

Tail/ Stop Lamp 12V-0.2/2.1W (LED)

Turn Signal Lamp 12V-10Wx4 MFR (Amber bulb

with clear lens)

DIMENSIONS & WEIGHTS

Length x Width x Height 2222 x 850 x 1258 mm

Wheelbase 1410 mm

Ground Clearance 220 mm

Fuel Tank Capacity 13 Liter

Kerb Weight 154KG